



BS EN 14351-1:2006+A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

DECLARATION OF PERFORMANCE

THIS IS TO CERTIFY THAT



91a

Romney Avenue

Bristol

BS7 9ST

HAVE CONFORMED WITH EN 14351-1:A1:2010 ANNEX ZA

FOR

VERTICAL SLIDING & CASEMENT WINDOWS AND DOORS INTENDED TO BE USED IN
DOMESTIC AND COMMERCIAL LOCATIONS

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION CONTROL
COMPLYING WITH EN 14351-1:A1:2010 ANNEX ZA

PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORT AND PERFORMANCE
INDICATION PAPERS FOR ALL COMPONENTS

INCLUDING THE FOLLOWING MANDATORY REQUIREMENTS

LOAD BEARING CAPACITY OF SAFETY DEVICES - Clause 4.8

THERMAL CHARACTERISTICS - Clause 4.12

DANGEROUS SUBSTANCES - Clause 4.6

Signed: 
Position: Director

Date: 09-06-14



91a

Romney Avenue

Bristol

BS7 9ST

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: PVCu or Timber Windows and Doors

| <u>Characteristics</u> | Declared Value |
|---|--------------------|
| Dangerous Substances | None |
| Thermal Transmittance | $\leq 3.4W/(m^2K)$ |
| Load Bearing Capacity of Safety Devices | Passed |
| Resistance to Wind Load | npd |
| Resistance to snow and permanent load | npd |
| Reaction to fire | npd |
| External Fire Performance | npd |
| Watertightness | npd |
| Impact Resistance | npd |
| Radiation Properties | npd |
| Accoustic Performance | npd |
| Air Permiability | npd |
| | |

This declaration relates to a worst case scenario and as such all our products will give an equal to or better than performance to those quoted

Signed:.....

Date: 09-06-14

Position: Director



91a

Romney Avenue

Bristol

BS7 9ST

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: Metal Windows and Doors with no thermal break

| <u>Characteristics</u> | <u>Declared Value</u> |
|---|-----------------------|
| Dangerous Substances | None |
| Thermal Transmittance | $\leq 4.2W/(m^2K)$ |
| Load Bearing Capacity of Safety Devices | Passed |
| Resistance to Wind Load | npd |
| Resistance to snow and permanent load | npd |
| Reaction to fire | npd |
| External Fire Performance | npd |
| Watertightness | npd |
| Impact Resistance | npd |
| Radiation Properties | npd |
| Accoustic Performance | npd |
| Air Permiability | npd |
| | |

This declaration relates to a worst case scenario and as such all our products will give an equal to or better than performance to those quoted

Signed: 

Date: 09-06-14

Position: Director